

## Description

Fastener Length: ", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	3D0068310
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-449-3841
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



## P/N 3D0068-3-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.558 Inches Maximum
<b>Fastener Length:</b>	0.620 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.338 Inches Minimum And 0.381 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type Iii
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Titanium Alloy Uns R56400
<b>Screw Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response
<b>Bearing Surface Of Head Surface Finish:</b>	63.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0068-3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.