

Description

Fastener Length: ", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3D0068310
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-449-3841
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N 3D0068-3-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.558 Inches Maximum
Fastener Length:	0.620 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Titanium Alloy Uns R56400
Screw Material Document And Classification:	Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0068-3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.