

Description

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | 3D0068316 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-417-6447 |



P/N 3D0068-3-16 Specifications

| | |
|----------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.910 Inches Maximum |
| Fastener Length: | 0.970 Inches Minimum And 1.000 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.338 Inches Minimum And 0.381 Inches Maximum |
| Internal Drive Style: | Cross Recess Type Iii |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Titanium Alloy Uns R56400 |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0068-3-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.