

## P/N 3D0068-3-18

### **Description**

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 3D0068318

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-386-3101

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N 3D0068-3-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.916 Inches Minimum And 1.038 Inches Maximum
Fastener Length:	1.060 Inches Minimum And 1.120 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.381 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Titanium Alloy Uns R56400
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/3D0068-3-18">https://military-fasteners.com/screws/machine+screws/3D0068-3-18</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/3D0068-3-18">https://military-fasteners.com/screws/machine+screws/3D0068-3-18</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/3D0068-3-18">https://military-fasteners.com/screws/machine+screws/3D0068-3-18</a> and selecting the quantity you want then click "add to cart".