

Description

Fastener Length: 3-3/32", Thread: 3/4-16, Thread Length: 1-7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3D00731230
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-382-1156
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N 3D0073-12-30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.231 Inches Maximum
Fastener Length:	3.106 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.590 Inches Minimum And 0.610 Inches Maximum
Extended Washer Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
Extended Washer Thickness:	0.094 Inches Nominal
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Head Minor Diameter:	0.797 Inches Minimum And 0.812 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	1.865 Inches Minimum And 1.885 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3D0073-12-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.