

Description

Fastener Length: 5-3/64", Thread: 7/8-14, Thread Length: 1-13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | 3D00731458 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-465-3823 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N 3D0073-14-58 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.414 Inches Maximum |
| Fastener Length: | 5.024 Inches Minimum And 5.054 Inches Maximum |
| Head Style: | Spline Extended Washer |
| Head Height: | 0.700 Inches Nominal |
| Extended Washer Diameter: | 1.615 Inches Minimum And 1.625 Inches Maximum |
| Extended Washer Thickness: | 0.120 Inches Nominal |
| Grip Diameter: | 0.8730 Inches Minimum And 0.8740 Inches Maximum |
| Head Minor Diameter: | 0.923 Inches Minimum And 0.938 Inches Maximum |
| Nominal Thread Diameter: | 0.875 Inches |
| Grip Length: | 3.615 Inches Minimum And 3.635 Inches Maximum |
| Thread Quantity Per Inch: | 14 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Minimum Yield Strength: | 125000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Grip |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3D0073-14-58> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.