



Military-Fasteners.com

P/N 3D0073-5-18

Description

Fastener Length: 1-55/64", Thread: 1/4-24, Thread Length: 23/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3D0073518
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-425-3052
Schedule B:	7508.90.5000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N 3D0073-5-18 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.719 Inches Maximum
<b>Fastener Length:</b>	1.829 Inches Minimum And 1.859 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Extended Washer Diameter:</b>	0.575 Inches Minimum And 0.585 Inches Maximum
<b>Extended Washer Thickness:</b>	0.035 Inches Minimum And 0.055 Inches Maximum
<b>Grip Diameter:</b>	0.3110 Inches Minimum And 0.3120 Inches Maximum
<b>Head Minor Diameter:</b>	0.360 Inches Minimum And 0.375 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.115 Inches Minimum And 1.135 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	175000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Ams 5662 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3D0073-5-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.