

Description

Fastener Length: 2-9/32", Thread: 1/2-20, Thread Length: 29/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3D0073822 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-01-350-0648 |
| Schedule B: | 7508.90.5000 |
| ECCN: | 9A991 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE
AVAILABLE

P/N 3D0073-8-22 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.908 Inches Nominal |
| Fastener Length: | 2.273 Inches Minimum And 2.293 Inches Maximum |
| Head Style: | Spline Extended Washer |
| Head Height: | 0.440 Inches Minimum And 0.460 Inches Maximum |
| Extended Washer Diameter: | 0.922 Inches Minimum And 0.932 Inches Maximum |
| Extended Washer Thickness: | 0.062 Inches Minimum And 0.082 Inches Maximum |
| Grip Diameter: | 0.4985 Inches Minimum And 0.4995 Inches Maximum |
| Head Minor Diameter: | 0.547 Inches Minimum And 0.562 Inches Maximum |
| Nominal Thread Diameter: | 0.500 Inches |
| Grip Length: | 1.365 Inches Minimum And 1.385 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3D0073-8-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.