

Description

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3D0080312
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-381-1902
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N 3D0080-3-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	1.113 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.3206 Inches Minimum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	129.0 Degrees Minimum And 131.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0080-3-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.