



Military-Fasteners.com

P/N 3D0080-3-6

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3D008036
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-332-7156
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N 3D0080-3-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.363 Inches Nominal
Fastener Length:	0.723 Inches Minimum And 0.753 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.321 Inches Minimum And 0.405 Inches Maximum
Head Height:	0.010 Inches Minimum And 0.020 Inches Maximum
Grip Diameter:	0.375 Nominal Inches
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.365 Nominal Mils And 0.385 Nominal Centimeters
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2000 Pounds Per Square Inch
Countersink Angle:	129.0 Degrees Minimum And 131.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Screw, Machine 130 Deg Fl Hd Ms14191 Recess 95 Ksi Fsu Ti
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0080-3-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.