

**Description**

Fastener Length: 23/32", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3D008045
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-332-7124
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE  
AVAILABLE

## P/N 3D0080-4-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.403 Inches Nominal
<b>Fastener Length:</b>	0.700 Inches Minimum And 0.730 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.4421 Inches Minimum And 0.5260 Inches Maximum
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	129.0 Degrees Minimum And 131.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0080-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.