

## P/N 3D0080-5-7

## **Description**

Fastener Length: 61/64", Thread: 1/4-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 3D008057

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-377-1628

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N 3D0080-5-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Nominal
Fastener Length:	0.924 Inches Minimum And 0.954 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.5353 Inches Minimum And 0.6192 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	129.0 Degrees Minimum And 131.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/3D0080-5-7">https://military-fasteners.com/screws/machine+screws/3D0080-5-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.