

Description

Fastener Length: 1-61/64", Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	3D0091V620
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-351-3283
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N 3D0091V6-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.8020 Inches Minimum And 1.9620 Inches Maximum
Head Style:	Flush Countersunk
Head Major Diameter:	0.7500 Inches Minimum And 0.8230 Inches Maximum
Grip Length:	1.2400 Inches Minimum And 1.2600 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.3750 Inches
Shear Strength:	21000 Double Pounds Per Square Inch
Countersink Angle:	102.0 Degrees Minimum And 103.0 Degrees Maximum
Special Features:	Sleeve Included
Material:	Titanium Alloy Uns R56400 Bolt
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Bolt
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3D0091V6-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.