

**Description**

Fastener Length: 1-61/64", Thread Size: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3D0091V620
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-351-3283
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N 3D0091V6-20 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.8020 Inches Minimum And 1.9620 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Head Major Diameter:</b>	0.7500 Inches Minimum And 0.8230 Inches Maximum
<b>Grip Length:</b>	1.2400 Inches Minimum And 1.2600 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.3750 Inches
<b>Shear Strength:</b>	21000 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	102.0 Degrees Minimum And 103.0 Degrees Maximum
<b>Special Features:</b>	Sleeve Included
<b>Material:</b>	Titanium Alloy Uns R56400 Bolt
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Bolt
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3D0091V6-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.