

Description

Fastener Length: 2-43/64", Thread: 1/2-20, Thread Length: 49/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3D0124C8D36 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-504-0203 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE
AVAILABLE

P/N 3D0124C8D36 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.770 Inches Nominal |
| Fastener Length: | 2.645 Inches Minimum And 2.685 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.328 Inches Minimum And 0.360 Inches Maximum |
| Width Between Flats: | 0.928 Inches Minimum And 0.940 Inches Maximum |
| Shoulder Diameter: | 0.620 Inches Minimum First Shoulder And 0.624 Inches Maximum First Shoulder |
| Shoulder Length: | 2.260 Inches Minimum First Shoulder And 2.280 Inches Maximum First Shoulder |
| End Item Identification: | F-22 |
| Nominal Thread Diameter: | 0.500 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 167 Pounds Per Square Inch |
| Shoulder Shape: | Round First Shoulder |
| Part Name Assigned By Controlling Agency: | Bolt,shoulder-hexagon Head,a286 |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall And Vsm 1327 Mfr Ref Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3D0124C8D36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.