

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | 3D01416 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-391-7916 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 3D0141-6 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Identification Code Color: | Orange |
| Collar Outside Diameter: | 0.355 Inches Minimum And 0.385 Inches Maximum |
| Collar Overall Height: | 0.445 Inches Minimum And 0.490 Inches Maximum |
| Lubrication: | Cetyl Alcohol And Solid Film |
| Collar Inside Diameter: | 0.208 Inches Minimum And 0.212 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Collar Style: | Threaded (break Off) Type |
| Special Features: | Collar Has Captive Washer. |
| Heat Treatment: | T-73 Solution Heat Treated Collar |
| Material: | Aluminum Alloy 7075 Body |
| Material: | Titanium Washer |
| Material Document And Classification: | Ams4902 Assn Std 1st Material Response Washer Or Mil-t-9046 Mil Spec 2nd Material Response Washer |
| Material Document And Classification: | Qq-a-225/9 Fed Spec Single Material Response Collar |
| Surface Treatment: | Anodize Collar |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Body |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 88277-3d0141 Manufacturers Standard |

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/3D0141-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.