

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	3D01418
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-391-7879
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 3D0141-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Orange
Collar Outside Diameter:	0.440 Inches Minimum And 0.470 Inches Maximum
Collar Overall Height:	0.540 Inches Minimum And 0.585 Inches Maximum
Lubrication:	Cetyl Alcohol And Solid Film
Collar Inside Diameter:	0.268 Inches Minimum And 0.272 Inches Maximum
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Collar Has Captive Washer
Heat Treatment:	T-73 Solution Heat Treated Collar
Material:	Aluminum Alloy 7075 Body
Material:	Titanium Washer
Material Document And Classification:	Ams4902 Assn Std 1st Material Response Washer Or Mil-t-9046 Mil Spec 2nd Material Response Washer
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Collar
Surface Treatment:	Anodize Collar
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Thread Series Designator:	Unjf
Specification/standard Data:	88277-3d0141 Manufacturers Standard

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/3D0141-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.