

P/N 3D0213-12

Military-Fasteners.com

#### Description

Fastener Length: 5/8", Thread: 6-32, Thread Length: 17/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	3D021312
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-423-0376
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



# P/N 3D0213-12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.253 Inches Nominal
Fastener Length:	0.625 Inches Nominal
Head Style:	Pan No. 2
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
First Diameter From Head:	0.084 Inches Minimum And 0.089 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.372 Inches Minimum And 0.382 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Externally Relieved Body Diameter Quantity:	1
Color:	Black Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-s-763, 300 Series Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/3D0213-12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.