

**Description**

Screw part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	3M1034V4816
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-216-6620
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 3M1034V4-8-16 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.444 Inches Minimum And 0.494 Inches Maximum
<b>Fastener Length:</b>	0.954 Inches Minimum And 0.984 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.497 Inches Minimum And 0.507 Inches Maximum
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	Thd Hole In Top Of Head 0.138-32 Unjc-3b Thd,hole 0.300 In. Min. 0.345 In. Max Dp,counterbore 0.145 In. Min. 0.150 In. Max Dia; Injection Port 0.120 In. Lg,0.060 In. Wide In Unthd Shank; Distance From Top Of Head To Beginning Of Injection Port 0.160 In.
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1034V4-8-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.