



Military-Fasteners.com

P/N 3M1034V4-9-21

Description

Fastener Length: 1-1/32", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1034V4921
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-217-5172
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N 3M1034V4-9-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	1.016 Inches Minimum And 1.046 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.497 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Thd Hole In Top Of Head 0.138-32 Unjc-3b Thd,hole 0.300 In. Min. 0.345 In. Max Dp,counterbore 0.145 In. Min. 0.150 In. Max Dia; Injection Port 0.120 In. Lg,0.060 In. Wide In Unthd Shank; Distance From Top Of Head To Beginning Of Injection Port 0.210 In.
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1034V4-9-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.