

Description

flush countersunk, dry film

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	3M10673300
Minimum Qty (MOQ):	5
NSN:	5320-01-173-3679
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N 3M1067-3-300 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.1970 Inches Minimum And 0.1985 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.385 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film Or Cetyl Alcohol Or Paraffin Wax
Grip Length:	0.250 Inches Minimum And 0.300 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Bolt
Material:	Steel Comp 303se Sleeve
Material:	Titanium Alloy Uns R56400 Nut
Material Document And Classification:	Ams 5641 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Nut Or Ams 4967 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Bolt Or Ams 5731 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Bolt
Surface Treatment:	Passivate Overall
Surface Treatment:	Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/3M1067-3-300> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.