

### Description

flush countersunk, dry film

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### Additional Information

SKU / Model:	3M10673300
Minimum Qty (MOQ):	5
NSN:	5320-01-173-3679
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N 3M1067-3-300 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.1970 Inches Minimum And 0.1985 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.385 Inches Maximum
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film Or Cetyl Alcohol Or Paraffin Wax
<b>Grip Length:</b>	0.250 Inches Minimum And 0.300 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Bolt
<b>Material:</b>	Steel Comp 303se Sleeve
<b>Material:</b>	Titanium Alloy Uns R56400 Nut
<b>Material Document And Classification:</b>	Ams 5641 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Nut Or Ams 4967 Assn Std Single Material Response Nut
<b>Material Document And Classification:</b>	Ams 5732 Assn Std Single Material Response Bolt Or Ams 5731 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Bolt
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment:</b>	Passivate Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Bolt
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/3M1067-3-300> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.