

## P/N 3M1100-02A

## **Description**

Fastener Length: 5/16", Thread: 2-56, Thread Length: 5/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 3M110002A

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-207-7544

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N 3M1100-02A Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.160 Inches Nominal
Fastener Length:	0.340 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.147 Inches Minimum And 0.153 Inches Maximum
Head Height:	0.037 Inches Minimum And 0.043 Inches Maximum
Shoulder Diameter:	0.103 Inches Minimum And 0.107 Inches Maximum First Shoulder
Shoulder Length:	0.165 Inches Minimum And 0.175 Inches Maximum First Shoulder
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/3M1100-02A">https://military-fasteners.com/screws/machine+screws/3M1100-02A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.