

Description

Fastener Length: 1-23/64", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1165315F
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-410-7235
Schedule B:	7508.90.5000
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N 3M1165-3-15F Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	1.319 Inches Minimum And 1.369 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.376 Inches Minimum And 0.385 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.938 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M1165-3-15F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.