

**Description**

Fastener Length: 43/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M1169C33AF
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-518-3301
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N 3M1169C3-3AF Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.345 Inches Nominal
<b>Fastener Length:</b>	0.643 Inches Minimum And 0.673 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.372 Inches Minimum And 0.381 Inches Maximum
<b>Spline Major Diameter:</b>	0.1540 Inches Minimum And 0.1560 Inches Maximum
<b>Grip Diameter:</b>	0.188 Inches Minimum And 0.189 Inches Maximum
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Torx
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.313 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Inconel 718;per Ams 5662 Mfr Ref 1st Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C3-3AF> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.