



Military-Fasteners.com

P/N 3M1169C3-3AF

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1169C33AF
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-518-3301
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N 3M1169C3-3AF Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.643 Inches Minimum And 0.673 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.372 Inches Minimum And 0.381 Inches Maximum
Spline Major Diameter:	0.1540 Inches Minimum And 0.1560 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Point Style:	Flat
Internal Drive Style:	Torx
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.313 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Inconel 718;per Ams 5662 Mfr Ref 1st Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C3-3AF> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.