

**Description**

Fastener Length: 43/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | 3M1169C33AF                   |
| Minimum Qty (MOQ):      | 5 EA                          |
| NSN:                    | 5305-01-518-3301              |
| Schedule B:             | 7508.90.5000                  |
| ECCN:                   | EAR99                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N 3M1169C3-3AF Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.345 Inches Nominal   |
| <b>Fastener Length:</b>                      | 0.643 Inches Minimum And 0.673 Inches Maximum                  |
| <b>Head Style:</b>                           | Flat Countersunk   |
| <b>Head Diameter:</b>                        | 0.372 Inches Minimum And 0.381 Inches Maximum                  |
| <b>Spline Major Diameter:</b>                | 0.1540 Inches Minimum And 0.1560 Inches Maximum                |
| <b>Grip Diameter:</b>                        | 0.188 Inches Minimum And 0.189 Inches Maximum                  |
| <b>Point Style:</b>                          | Flat   |
| <b>Internal Drive Style:</b>                 | Torx   |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 0.313 Inches Nominal   |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Countersink Angle:</b>                    | 99.0 Degrees Minimum And 101.0 Degrees Maximum                 |
| <b>Material:</b>                             | Steel Corrosion Resisting Overall                              |
| <b>Material Document And Classification:</b> | Inconel 718;per Ams 5662 Mfr Ref 1st Material Response Overall |
| <b>Thread Series Designator:</b>             | Unjf   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C3-3AF> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.