

**Description**

Fastener Length: 39/64", Thread: 10-32, Thread Length: 11/32",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M1169C34A
Minimum Qty (MOQ):	5
NSN:	5305-01-497-0857
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N 3M1169C3-4A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.345 Inches Nominal
<b>Fastener Length:</b>	0.580 Inches Minimum And 0.610 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.3729 Inches Minimum And 0.3813 Inches Maximum
<b>Spline Minor Diameter:</b>	0.1105 Inches Minimum And 0.1125 Inches Maximum
<b>Spline Major Diameter:</b>	0.1540 Inches Minimum And 0.1560 Inches Maximum
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Torx
<b>End Item Identification:</b>	F18 E/f
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, 100 Degree Tension Head, Gear Drive Recess
<b>Special Features:</b>	125 Ksi Shear Strength
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Material Document And Classification:</b>	Aams 5662 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C3-4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.