

**Description**

Fastener Length: 23/32", Thread: 10-32, Thread Length: 11/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M1169C36A
Minimum Qty (MOQ):	2
NSN:	5305-01-472-9735
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N 3M1169C3-6A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.720 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.372 Inches Minimum And 0.381 Inches Maximum
Spline Minor Diameter:	0.1105 Inches Minimum And 0.1125 Inches Maximum
Spline Major Diameter:	0.1540 Inches Minimum And 0.1560 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Point Style:	Flat
Internal Drive Style:	Torx
End Item Identification:	F18 E/f
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.375 Inches Nominal
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Bolt,100 Degree Tension Head,gear Drive Recess-ph13-8mo (125 Ksi Shear),inconel 718 (125 Ksi Shear),6al-4v Titanium (95 Ksi Shear)
Special Features:	125 Ksi Ulimate Shear Strength
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Inconel 718, Per 23-118 Mfr Ref 1st Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C3-6A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.