

Description

Fastener Length: 59/64", Thread: 10-32, Thread Length: 11/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1169C39A
Minimum Qty (MOQ):	5
NSN:	5305-01-534-4519
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N 3M1169C3-9A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.892 Inches Minimum And 0.922 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.372 Inches Minimum And 0.381 Inches Maximum
Spline Major Diameter:	0.154 Inches Minimum And 0.156 Inches Maximum
Grip Diameter:	0.189 Inches Nominal
Point Diameter:	0.345 Inches Nominal
Point Style:	Flat
Internal Drive Style:	Torx
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Degree Tension Head, Gear Drive Recess
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C3-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.