

Description

Fastener Length: 59/64", Thread: 10-32, Thread Length: 11/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | 3M1169C39A |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-534-4519 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N 3M1169C3-9A Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Nominal |
| Fastener Length: | 0.892 Inches Minimum And 0.922 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.372 Inches Minimum And 0.381 Inches Maximum |
| Spline Major Diameter: | 0.154 Inches Minimum And 0.156 Inches Maximum |
| Grip Diameter: | 0.189 Inches Nominal |
| Point Diameter: | 0.345 Inches Nominal |
| Point Style: | Flat |
| Internal Drive Style: | Torx |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Bolt, 100 Degree Tension Head, Gear Drive Recess |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C3-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.