

Description

Fastener Length: 1-1/4", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	3M1169C413A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-490-6858
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N 3M1169C4-13A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.420 Inches Minimum And 0.430 Inches Maximum
Fastener Length:	1.222 Inches Minimum And 1.252 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.497 Inches Minimum And 0.506 Inches Maximum
Spline Major Diameter:	0.154 Inches Minimum And 0.156 Inches Maximum
Grip Diameter:	0.249 Inches Nominal
Point Diameter:	0.425 Inches Nominal
Point Style:	Flat
Internal Drive Style:	Torx
End Item Identification:	F18 E/f Aircraft
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Degree Tension Head, Gear Drive Recess
Special Features:	125 Ksi Shear Strength
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-13A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.