

**Description**

Fastener Length: 2-", Thread: 1/4-28, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M1169C432A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-500-8224
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N 3M1169C4-32A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Nominal
<b>Fastener Length:</b>	2.000 Inches Nominal
<b>Head Style:</b>	Fillister Countersunk
<b>Head Diameter:</b>	0.470 Inches Minimum And 0.477 Inches Maximum
<b>Head Height:</b>	0.015 Inches Nominal
<b>Spline Major Diameter:</b>	0.221 Inches Nominal
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	Torx
<b>End Item Identification:</b>	Fighter,aircraft,first F18
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.250 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Criticality Code Justification:</b>	Aaur
<b>Special Features:</b>	Specific Matl Is Inconel 718 Cres
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-32A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.