



Military-Fasteners.com

P/N 3M1169C4-32A

Description

Fastener Length: 2-", Thread: 1/4-28, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | 3M1169C432A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-500-8224 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



* See page 2 for technical characteristics

P/N 3M1169C4-32A Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Nominal |
| Fastener Length: | 2.000 Inches Nominal |
| Head Style: | Fillister Countersunk |
| Head Diameter: | 0.470 Inches Minimum And 0.477 Inches Maximum |
| Head Height: | 0.015 Inches Nominal |
| Spline Major Diameter: | 0.221 Inches Nominal |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Torx |
| End Item Identification: | Fighter,aircraft,first F18 |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.250 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Criticality Code Justification: | Aaur |
| Special Features: | Specific Matl Is Inconel 718 Cres |
| Material: | Steel Corrosion Resisting Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-32A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.