

Description

Fastener Length: 2-", Thread: 1/4-28, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1169C432A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-500-8224
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N 3M1169C4-32A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Nominal
Fastener Length:	2.000 Inches Nominal
Head Style:	Fillister Countersunk
Head Diameter:	0.470 Inches Minimum And 0.477 Inches Maximum
Head Height:	0.015 Inches Nominal
Spline Major Diameter:	0.221 Inches Nominal
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	Fighter,aircraft,first F18
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.250 Inches Nominal
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Aaur
Special Features:	Specific Matl Is Inconel 718 Cres
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-32A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.