



Military-Fasteners.com

P/N 3M1169C4-34A

Description

Fastener Length: 2-9/16", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                       |
|-------------------------|-----------------------|
| SKU / Model:            | 3M1169C434A           |
| Minimum Qty (MOQ):      | 5 EA                  |
| NSN:                    | 5305-01-500-8228      |
| Schedule B:             | 7508.90.5000          |
| ECCN:                   | 9A991                 |
| National Motor Freight: | 095190, Hardware, Noi |



\* See page 2 for technical characteristics

## P/N 3M1169C4-34A Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                             | 3a   |
| <b>Thread Direction:</b>                         | Right-hand   |
| <b>Thread Length:</b>                            | 0.420 Inches Minimum And 0.430 Inches Maximum      |
| <b>Fastener Length:</b>                          | 2.535 Inches Minimum And 2.565 Inches Maximum      |
| <b>Head Style:</b>                               | Flat Countersunk                                   |
| <b>Head Diameter:</b>                            | 0.497 Inches Minimum And 0.506 Inches Maximum      |
| <b>Spline Major Diameter:</b>                    | 0.154 Inches Minimum And 0.156 Inches Maximum      |
| <b>Grip Diameter:</b>                            | 0.249 Inches Nominal                               |
| <b>Point Diameter:</b>                           | 0.425 Inches Nominal                               |
| <b>Point Style:</b>                              | Flat   |
| <b>Internal Drive Style:</b>                     | Torx   |
| <b>Nominal Thread Diameter:</b>                  | 0.250 Inches                                       |
| <b>Grip Length:</b>                              | 0.490 Inches Minimum And 0.510 Inches Maximum      |
| <b>Thread Quantity Per Inch:</b>                 | 28   |
| <b>Countersink Angle:</b>                        | 99.0 Degrees Minimum And 101.0 Degrees Maximum     |
| <b>Part Name Assigned By Controlling Agency:</b> | Bolt, 100 Degree Tension Head, Gear Drive Recess   |
| <b>Special Features:</b>                         | 125 Ksi Shear Strength                             |
| <b>Material:</b>                                 | Nickel Alloy 718 Overall                           |
| <b>Material Document And Classification:</b>     | Ams 5662 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                        | Passivate Overall                                  |
| <b>Thread Series Designator:</b>                 | Unjf   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-34A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.