

Description

Fastener Length: 63/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1169C49A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-476-9193
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N 3M1169C4-9A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	0.988 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.470 Inches Minimum And 0.477 Inches Maximum
Grip Diameter:	0.249 Inches Nominal
Internal Drive Style:	Torx
End Item Identification:	Structural Section
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.563 Inches Nominal
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Screw,close Tolerance
Material:	Nickel Alloy 718 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.