

Description

Fastener Length: 63/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-----------------------|
| SKU / Model: | 3M1169C49A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-476-9193 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi |

NO IMAGE
AVAILABLE

P/N 3M1169C4-9A Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 0.988 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.470 Inches Minimum And 0.477 Inches Maximum |
| Grip Diameter: | 0.249 Inches Nominal |
| Internal Drive Style: | Torx |
| End Item Identification: | Structural Section |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.563 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Criticality Code Justification: | Agav |
| Part Name Assigned By Controlling Agency: | Screw,close Tolerance |
| Material: | Nickel Alloy 718 Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.