

**Description**

Fastener Length: 63/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M1169C49AF
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-481-9323
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

## P/N 3M1169C4-9AF Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	0.988 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.470 Inches Minimum And 0.477 Inches Maximum
<b>Grip Diameter:</b>	0.249 Inches Nominal
<b>Internal Drive Style:</b>	Torx
<b>End Item Identification:</b>	Pylon,aircraft, F/a-18(e/f)
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.563 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Criticality Code Justification:</b>	Agav
<b>Part Name Assigned By Controlling Agency:</b>	Screw,close Tolerance
<b>Material:</b>	Nickel Alloy 718 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C4-9AF> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.