

Description

Fastener Length: 59/64", Thread: 5/16-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | 3M1169C57A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-529-4182 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N 3M1169C5-7A Specifications

| | |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.469 Inches Nominal |
| Fastener Length: | 0.907 Inches Minimum And 0.922 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.6230 Inches Minimum And 0.6335 Inches Maximum |
| Spline Minor Diameter: | 0.1570 Inches Minimum And 0.1600 Inches Maximum |
| Spline Major Diameter: | 0.2195 Inches Minimum And 0.2225 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | Torx |
| End Item Identification: | F18 E/f |
| Nominal Thread Diameter: | 0.3125 Inches |
| Grip Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Criticality Code Justification: | Agav |
| Part Name Assigned By Controlling Agency: | Bolt,100 Degree Tension Head Gear Drive Recess-ph13-8mo (125 Ksi Shear),inconel 718 (125 Ksi Shear), 6al-4v Titanium (95 Ksi Shear) |
| Special Features: | 125 Ksi Ultimate Shear Strength |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C5-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.