

Description

Fastener Length: 59/64", Thread: 5/16-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1169C57A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-529-4182
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N 3M1169C5-7A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	0.907 Inches Minimum And 0.922 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.6230 Inches Minimum And 0.6335 Inches Maximum
Spline Minor Diameter:	0.1570 Inches Minimum And 0.1600 Inches Maximum
Spline Major Diameter:	0.2195 Inches Minimum And 0.2225 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	F18 E/f
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Bolt,100 Degree Tension Head Gear Drive Recess-ph13-8mo (125 Ksi Shear),inconel 718 (125 Ksi Shear), 6al-4v Titanium (95 Ksi Shear)
Special Features:	125 Ksi Ultimate Shear Strength
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M1169C5-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.