

Description

Fastener Length: 1-7/64", Thread: 1/4-24, Thread Length: 15/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1170C510A
Minimum Qty (MOQ):	5
NSN:	5305-01-526-3950
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N 3M1170C5-10A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.464 Inches Minimum And 0.474 Inches Maximum
Fastener Length:	1.079 Inches Minimum And 1.109 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.464 Inches Minimum And 0.473 Inches Maximum
Spline Major Diameter:	0.154 Inches Minimum And 0.156 Inches Maximum
Grip Diameter:	0.312 Inches Nominal
Point Diameter:	0.469 Inches Nominal
Point Style:	Flat
Internal Drive Style:	Torx
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Degree Reduced Head, Gear Drive Recess
Special Features:	125 Ksi Shear Strength
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/3M1170C5-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.