

Description

Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	3M123838
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-512-0492
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N 3M1238-3-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Locking Feature:	Slotted Locking Feature
End Item Identification:	Aircraft, F18 E/f
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.500 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2420 Pounds Per Square Inch
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Inavy) Fastener, Hex Head; Fastener-captive, Hex Head
Special Features:	Having 2 Key-way Slots On The Shank 180 Degrees Out
Material:	Steel Overall
Material Document And Classification:	A286 Per Ams 5731 Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M1238-3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.