

Description

Fastener Length: 9/16", Hole Diameter: 1/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1275E3D4A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-597-9677
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M1275E3D4A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.315 Inches Nominal
Fastener Length:	0.563 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.3729 Inches Minimum And 0.3813 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.2021 Inches Minimum And 0.2026 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.248 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Round
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-I-87132, Type I, Class B Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3M1275E3D4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.