



Military-Fasteners.com

P/N 3M1276E6D12A

Description

Bolt part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1276E6D12A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-606-0832
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M1276E6D12A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	1.313 Inches Minimum And 1.333 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.724 Inches Minimum And 0.731 Inches Maximum
Grip Diameter:	0.4052 Inches Minimum And 0.4057 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
End Item Identification:	Various Navy Components
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.603 Inches Nominal
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Agav
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.218 Inches Nominal First Hole
Part Name Assigned By Controlling Agency:	Bolt,100 Deg Tension Head,gear Drive Recess
Special Features:	Item Used For Repair Only; 125 Ksi Shear
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Sae Ams5682 Inconel 718 National Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-I-87132,ty I,gr B Mil Spec Single Treatment Response Overall
Supplementary Features:	Item Furnished W/torq Drive Socket; 0.0312 Inch Oversize
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3M1276E6D12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.