



Military-Fasteners.com

P/N 3M1277E3D3A

Description

Fastener Length: 37/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M1277E3D3A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-536-4441 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N 3M1277E3D3A Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.330 Inches Minimum And 0.360 Inches Maximum |
| Fastener Length: | 0.518 Inches Minimum And 0.588 Inches Maximum |
| Head Style: | Fillister Countersunk |
| Head Diameter: | 0.265 Inches Minimum And 0.272 Inches Maximum |
| Head Height: | 0.042 Inches Nominal |
| Grip Diameter: | 0.2021 Inches Minimum And 0.2026 Inches Maximum |
| End Item Identification: | F/a-18 Aircraft |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Criticality Code Justification: | Agav |
| Part Name Assigned By Controlling Agency: | Bolt,100 Deg Reduced Head,gear Drive Recess,inconel 718 (125 Ksi Shear),0.0156 Inch Oversize |
| Special Features: | Internal Drive Recess Per Nas 1800 |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams 5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-I-87132,ty 1,gr B Mil Spec Single Treatment Response Overall |
| Supplementary Features: | Cotter Pin Hole 0.070 Inch Dia At Tip Of Bolt 0.106 Inch From End |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3M1277E3D3A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.