



Military-Fasteners.com

P/N 3M1277E3D6A

Description

Bolt part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1277E3D6A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-536-4430
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M1277E3D6A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.330 Inches Minimum And 0.360 Inches Maximum
Fastener Length:	0.705 Inches Minimum And 0.735 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.265 Inches Minimum And 0.272 Inches Maximum
Head Height:	0.042 Inches Nominal
Grip Diameter:	0.2021 Inches Minimum And 0.2026 Inches Maximum
End Item Identification:	F/a-18 Aircraft
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Bolt,100 Deg Reduced Head,gear Drive Recess,inconel 718 (125 Ksi Shear),0.0156 Inch Oversize
Special Features:	Internal Drive Recess Per Nas 1800
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-I-87132,ty 1,gr B Mil Spec Single Treatment Response Overall
Supplementary Features:	Cotter Pin Hole 0.070 Inch Dia At The Tip Of The Bolt 0.106 Inch From The End
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3M1277E3D6A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.