

P/N 3M1277E5D10A

Military-Fasteners.com

Description

Fastener Length: 1-3/32", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | 3M1277E5D10A |
|-------------------------|---|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-599-4562 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N 3M1277E5D10A Specifications

| Thread Class: | За |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.469 Inches Nominal |
| Fastener Length: | 1.094 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.4645 Inches Minimum And 0.4739 Inches Maximum |
| Hole Diameter: | 0.076 Inches Nominal |
| Grip Diameter: | 0.3271 Inches Minimum And 0.3276 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.625 Inches Nominal |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Hole Configuration Style: | Round |
| Countersink Angle: | 90.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Nickel Alloy 718 Overall |
| Material Document And Classification: | Ams5662 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-I-87132, Type 1, Grade B Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/3M1277E5D10A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.