



Military-Fasteners.com

P/N 3M1277E5D6A

Description

Fastener Length: 27/32", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M1277E5D6A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-599-4554
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M1277E5D6A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	0.844 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.4645 Inches Minimum And 0.4739 Inches Maximum
Hole Diameter:	0.076 Inches Nominal
Grip Diameter:	0.3271 Inches Minimum And 0.3276 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.375 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hole Configuration Style:	Round
Countersink Angle:	90.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-I-87132, Type 1, Grade B Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3M1277E5D6A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.