

## P/N 3M1278E4D9A

## **Description**

Fastener Length: 0-63/64", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: 3M1278E4D9A

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-536-4445

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N 3M1278E4D9A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	0.9725 Inches Minimum And 1.0025 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.388 Inches Minimum And 0.395 Inches Maximum
Shoulder Diameter:	0.2802 Inches Minimum Grip And 0.2807 Inches Maximum Grip
Shoulder Length:	0.5025 Inches Nominal Grip
Hole Diameter:	0.076 Inches Minimum And 0.086 Inches Maximum
Spline Minor Diameter:	0.1105 Inches Minimum And 0.1125 Inches Maximum
Spline Major Diameter:	0.1540 Inches Minimum And 0.1560 Inches Maximum
Internal Drive Style:	Torx
End Item Identification:	F/a 18 E/f Aircraft
Nominal Thread Diameter:	0.2500 Inches
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Cetyl Alcohol Lubricant
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Agav
Shoulder Shape:	Round Grip
Part Name Assigned By Controlling Agency:	Eddie Bolt Aircraft
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5662 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-l-87132 Type 1 Grade B Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

